

MY24 TRAXTER PRO XU HD10 T ABS



Tundra Green
 Timeless Black

ENGINE	HD10
Type	61 kW (82 hp) / 69 lb-ft, Rotax® 976 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTCTM) with Electronic Fuel Injection (EFI)
Transmission	PRO-TORQ CVT Transmission with Quick Response System (QRS), high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P
Drive Train	Selectable Turf Mode / 2WD / 4WD with Open front differential with ABS system
Driving Assistance	Electronic Hill Descent Control ECO™ / ECO™ Off / Work modes Brake holding mechanism
Power Steering	Dynamic Power Steering (DPS)
Speed Category	More than 60 km/h

SUSPENSIONS	
Front Suspension	Arched double A-arm / 11 in. (27.9 cm) travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	Arched TTA with external sway bar / 11 in. (27.9 cm) travel
Rear Shocks	Twin tube gas charged shocks

TIRES	
Front Tires / Rear Tires	Maxxis Coronado† 27 x 9 / 11 x 14 in. (68.6 x 22.9 / 27.9 x 35.6 cm)
Wheels	14 in. (35.6 cm) cast-aluminum

BRAKES	
Front	Dual 220 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm disc brakes with hydraulic twin-piston calipers

HIGHLIGHTS

- Dynamic Power Steering (DPS)
- Anti-Lock Braking System (ABS)
- 14 in. (35.6 cm) cast-aluminum wheels
- 27 in. (68.6 cm) Maxxis Coronado† tires
- 4,500-lb (2,041 kg) winch
- RF Digitally Encoded Security System (D.E.S.S.™)
- Heater-ready

DIMENSIONS / CAPACITIES

Cage	Profiled cage. ROPS approved
Estimated Dry Weight*	1,964 lb (891 kg)
L x W x H	154.1 x 64 x 78 (391.5 x 162.5 x 198.1 cm)
Wheelbase	115.5 in. (294 cm)
Ground Clearance	12.5 in. (32 cm)
Cargo Box Dimensions	72 x 54.5 x 10 in. (180.3 x 138.4 x 25.4 cm)
Cargo Box Capacity	1,200 lb (544 kg)
Power tilt bed	N/A
Tailgate Load Capacity	250 lb (113.4 kg)
Storage Capacity	Total: 94 gal (356 L)
Towing Capacity	2,500 lb (1136 kg)
Payload Capacity	1700 lb (771 kg)
Fuel Capacity	10.6 gal (40 L)
Person Capacity	3

FEATURES

Gauge	7.6 in. (19.3 cm) wide digital display with keypad
Battery	12-V (30 amp/h)
Magneto	650-W
Instrumentation	DC outlet (10-A)
Lighting	Front lighting output 140 W LED tail lights
Winch	4,500-lb (2,041 kg) winch with roller fairlead
Seat	VERSA-PRO bench seat with passenger seats flipping up, underside hooks, reinforced seat skin
Steering Wheel	Adjustable tilt steering
Protection	Integrated front steel bumper HMWPE full skid plate Front fender extension
Anti-Theft System	RF Digitally Encoded Security System
Hitch Type	2-in hitch receiver with rear hitch, tow ball and trailer connexion
T-Cat Features	Horn, flashers and position lamps, side mirrors, license plate support, hook on front metal bumper

WARRANTY

Factory warranty	2-year BRP limited warranty
------------------	-----------------------------



©2024 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of BRP or its affiliates. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrives GmbH. ‡All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all SSV drivers take a training course. For safety and training information, see your dealer. SSVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. SSVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any SSV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.



A BRP BRAND

REQUEST A QUOTE



MY24 TRAXTER PRO XU HD10 T ABS



■ Tundra Green
■ Timeless Black

MOTOR	HD10
Tip	61 kW (82 hp) / 69 lb-ft, Rotax® 976 cc, V-twin, sıvı soğutmalı
Yakıt Dağıtım Sistemi	Elektronik Yakıtlı Akıllı Gaz Kelebeği Kontrolü (iTC™) Enjeksiyon (EFI)
Aktarma	Hızlı Tepsi Sistemi PRO-TORQ CVT Şanzıman (QRS), Yüksek hava akışı havalandırması ve Elektronik Tahrik Kayışı Extra L / H / N / R / P
Güç Aktarımı	ABS Sistemli, Açık ön diferansiyelli, Seçilebilir Çim Modu / 2WD / 4WD
Sürüş Asistanı	Elektronik İniş Sistemi ECO™ / ECO™ Kapalı / Çalışma Modları Fren tutam mekanizması
Hidrolik Direksiyon	Dinamik Servo Direksiyon (DPS™)
Hız Kategorisi	60 km/h saatten fazla

SÜSPANSİYONLAR

Ön Süspansiyon	Kemerli Çift A Kolu 11 inç. (27,9 cm) hareket mesafesi
Ön Şoklar	İkiz tüplü şarjlı şoklar
Arka Süspansiyon	Harici sallanma şubüğüne sahip Kemerli TTA / 11 inç. (27,9cm) hareket mesafesi
Arka Şoklar	Çift tüplü gaz şarjlı şoklar

LASTİKLER / TEKERLEKLER

Ön Lastikler / Arka Lastikler	Maxxis Coronado† 27 x 9 / 11 x 14 in. (68.6 x 22.9 / 27.9 x 35.6 cm)
Tekerlekler	14 inç. (35,6 cm) dökme alüminyum

FRENLER

Ön	Hidrolik çift pistonlu kaliberlere sahip çift 220 mm disk frenler
Arka	Hidrolik çift pistonlu kaliberlere sahip çift 220 mm disk frenler

ÖNE ÇIKAN ÖZELLİKLER

- Dinamik Servo Direksiyon (DPS)
- Kilitlenmeyi Önleyici Fren Sistemi (ABS)
- 14 inç (35,6 cm) dökme alüminyum tekerlekler
- 27 inç (68,6 cm) Maxxis Coronado† lastikler
- 4,500-lb (2,041 kg) vinç
- RF Dijital Kodlu Güvenlik Sistemi (D.E.S.S.™)
- Isıtıcıya hazır

BOYUTLAR / KAPASİTELER

Kafes	Profilli kafes ROPS onaylı
Tahmini Kuru Ağırlık *	1.964 lb (891 kg)
Ux G x Y	154.1 x 64 x 78 (391,5 x 162.5 x 198.1 cm)
Dingil Açıklığı	115.5 inç (294 cm)
Yerden Yükseklik	12.5 inç (32 cm)
Kargo Kutusu Boyutları	72 x 54.5 x 10 inç. (180,3 x 138.4 x 25.4 cm)
Kargo Kutusu Kapasitesi	1,200 lb (544 kg)
Güç Eğimli Yatak	N/A
Bagaj Kapağı Yük Kapasitesi	250 lb (113.4 kg)
Depolama Kapasitesi	Toplam 94 galon (356 L)
Çekme Kapasitesi	2,500 lb (1136 kg)
Yük Kapasitesi	1,700 lb (771 kg)
Yakıt Kapasitesi	10.6 gal (40 L)
Kişi Kapasitesi	3

ÖZELLİKLER

Ölçü	7.6 inç (19.3 cm) genişliğinde tuş takımlı dijital ekran
Akü	12-V (30 amp/h)
Şarj Dinamosu	650-W
Enstrümantasyon	DC çıkışı (10-A)
Aydınlatma	Ön aydınlatma çıkışı 140 W LED arka lambalar
Vinç	Makaralı 4,500-lb (2,041 kg) vinç
Koltuk	Yukarıya doğru kaldırılabilen yolcu koltukları, alt tarafta kancaları ve güçlendirilmiş koltuk kaplaması olan VERSA-PRO koltuk sırası
Direksiyon	Ayarlanabilir eğimli direksiyon
Koruma	Entegre ön çelik tampon HMWPE tam koruma plakası Ön çamurluk uzatması
Hırsızlık Önleme Sistemi	RF Dijital Kodlu Güvenlik Sistemi
Bağlantı Tipi	Arka askı, çeki topuzu ve römork bağlantısına sahip 2 inç askı alıcısı
T-Cat Özellikleri	Korna flaşörler ve pozisyon lambaları, yan aynalar, plaka desteği, ön metal tamponda kanca

GARANTİ

2-Yıl

can-am

BRP -Lynx-Ski Doo / T.C. Kamu Temsilcisi



arem
savunma lojistik

Web Adres
E-Posta

Telefon

: www.aremlojistik.com
: emrearslan@aremlojistik.com
: info@aremlojistik.com
: +90 212 602 AREM



MY23 TRAXTER PRO DPS HD10



Tundra Green

ENGINE

Type	61 kW (82 hp) / 69 lb-ft, Rotax® 976 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (ITC™) with Electronic Fuel Injection (EFI)
Transmission	PRO-TORQ CVT Transmission with Quick Response System (QRS), high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P
Drive Train	Selectable Turf Mode / 2WD / 4WD with Visco-Lok† auto-locking front differential
Driving Assistance	Electronic Hill Descent Control ECO™ / ECO™ Off / Work modes
Power Steering	Dynamic Power Steering (DPS™)

SUSPENSIONS

Front Suspension	Arched double A-arm / 11 in. (27.9 cm) travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	Arched TTA with external sway bar / 11 in. (27.9 cm) travel
Rear Shocks	Twin tube gas charged shocks

TIRES / WHEELS

Front & Rear Tires	XPS Trail King 27 x 9 / 11 x 14 in. (68.6 x 22.9 / 27.9 x 35.6 cm)
Wheels	14 in. (35.6 cm) cast-aluminum

BRAKES

Front	Dual 220 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm disc brakes with hydraulic twin-piston calipers

HIGHLIGHTS

- Dynamic Power Steering (DPS)
- 64 in. (162.5 cm) wide with Arched A-arm
- 14 in. (35.6 cm) cast-aluminum wheels
- 27 in. (68.6 cm) XPS Trail King tires
- Horn & side mirrors

DIMENSIONS / CAPACITIES

Cage	Profiled cage. ROPS approved
Estimated Dry Weight *	1,815 lb (823 kg)
L x W x H	154.1 x 64 x 78 (391.5 x 162.5 x 198.1 cm)
Wheelbase	115.5 in. (294 cm)
Ground Clearance	13 in. (33 cm)
Cargo Box Dimensions	72 x 54.5 x 10 in. (180.3 x 138.4 x 25.4 cm)
Cargo Box Capacity	1,000 lb (454 kg)
Power tilt bed	N/A
Tailgate Load Capacity	250 lb (113.4 kg)
Storage Capacity	Total: 94 gal (356 L)
Towing Capacity	2,500 lb (1136 kg)
Payload Capacity	1,570 lb (712 kg)
Fuel Capacity	10.6 gal (40 L)
Person Capacity	3

FEATURES

Gauge	4.5 in. (11.4 cm) wide digital display
Battery	12-V (18 amp/h)
Magneto	650-W
Instrumentation	DC outlet (10-A)
Lighting	Front lighting output 140 W LED tail lights
Winch	N/A
Seat	VERSA-PRO bench seat with passenger seats flipping up, underside hooks
Steering Wheel	Adjustable tilt steering
Protection	Integrated front steel bumper HMWPE central skid plate
Hitch Type	2-in hitch receiver

WARRANTY

Factory warranty	2-year BRP limited warranty
------------------	-----------------------------



©2022 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of BRP or its affiliates. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. ‡All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all SSV drivers take a training course. For safety and training information, see your dealer. SSVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. SSVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any SSV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.



MY23 TRAXTER PRO DPS HD10



Tundra Yeşili

MOTOR

Tip	61 kW (82 hp) / 69 lb-ft, Rotax® 976 cc, V-twin, sıvı soğutmalı
Yakıt Dağıtım Sistemi	Akıllı Gaz Kontrolü (iTC™) Elektronik Yakıt Enjeksiyonlu (EFI)
Aktarma	PRO-TORQ CVT Hızlı Tepki Sistemi (QRS), Yüksek Hava Akışlı Havalandırma ve Elektronik Tahrik Kayışı Koruması Ekstra L / H / N / R / P
Sürüş Treni	Selectable Turf Mode / 2WD / 4WD with Visco-Lok® auto-locking front differential
Sürüş Asistanı	Electronic Hill Descent Control ECO™ / ECO™ Off / Work modes
Hidrolik Direksiyon	Dinamik Servo Direksiyon (DPS™)

SÜSPANSİYONLAR

Ön Süspansiyonlar	Arched double A-arm / 11 in. (27.9 cm) travel
Ön Amortisörler	İkiz tüp gaz şarjlı şoklar
Arka Süspansiyonlar	Harici sallanma çubuğu / 11 inç (27,9 cm) hareket ile kemerli TTA
Arka Amortisörler	İkiz tüp gaz şarjlı şoklar

LASTİKLER / TEKERLEKLER

Ön Lastikler / Arka Lastikler	XPS Trail King 27 x 9 / 11 x 14 in. (68.6 x 22.9 / 27.9 x 35.6 cm)
Tekerlekler	14 in. (35.6 cm) Dökme Alüminyum

FRENLER

Ön	Hidrolik çift pistonlu kaliperli çift 220 mm disk frenler
Arka	Hidrolik tek pistonlu kaliperli çift 220 mm disk frenler

ÖNE ÇIKAN ÖZELLİKLER

- Dinamik Servo Direksiyon (DPS)
- 64 inç (162.5 cm) Genişliğinde ve Kemerli A kolu
- 14 inç (35.6 cm) dökme alüminyum jantlar
- 27 inç (68.6 cm) XPS Trail King lastikler
- Korna ve yan aynalar

BOYUTLAR / KAPASİTELER

Kafes	Profilli kafes. ROPS onaylı
Tahmini Kuru Ağırlık	1,815 lb (823 kg)
U x G x Y	154.1 x 64 x 78 (391.5 x 162.5 x 198.1 cm)
Dingil Açıklığı	115.5 in. (294 cm)
Yerden Yükseklik	13 in. (33 cm)
Kargo Kutusu Boyutları	72 x 54.5 x 10 in. (180.3 x 138.4 x 25.4 cm)
Kargo Kutusu Kapasitesi	1,000 lb (454 kg)
Güç Eğimli Yatak	N/A
Bagaj Kapağı Yük Kapasitesi	250 lb (113.4 kg)
Depolama Kapasitesi	Total: 94 gal (356 L)
Çekme Kapasitesi	2,500 lb (1136 kg)
Yük Kapasitesi	1,570 lb (712 kg)
Yakıt Kapasitesi	10.6 gal (40 L)
Kişi Kapasitesi	3

ÖZELLİKLERİ

Ölçü	4.5 in. (11.4 cm) Genişliğinde Dijital Ekran
Akü	12-V (18 amp/h)
Şarj Dinamosu	650-W
Enstrümantasyon	DC Çıkışlı (10-A)
Aydınlatma	Ön aydınlatma çıkışı 140 W LED arka lambalar
Vinç	N/A
Koltuk	Yukarı çevrilmiş yolcu koltukları, alt kancalar, güçlendirilmiş koltuk kaplaması ile VERSA-PRO koltuk sırası
Direksiyon	Ayarlanabilir eğimli direksiyon
Koruma	Entegre ön çelik tampon HMWPE tam koruma plakası
Bağlantı Tipi	2 inç askı alıcısı

GARANTİ

2- Yıl

BRP -Lynx-Ski Doo / T.C. Kamu Temsilcisi



arem
savunma lojistik

Web Adres
E-Posta

Telefon

: www.aremlojistik.com
: emrearslan@aremlojistik.com
info@aremlojistik.com
: +90 212 602 AREM



MY23 TRAXTER XU HD10 T



Timeless Black

ENGINE

Type	61 kW (82 hp) / 69 lb-ft, Rotax® 976 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PRO-TORQ CVT Transmission with Quick Response System (QRS), high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P
Drive Train	Selectable Turf Mode / 2WD / 4WD with Open front differential with ABS system
Driving Assistance	Electronic Hill Descent Control ECO™ / ECO™ Off / Work modes Brake holding mechanism
Power Steering	Dynamic Power Steering (DPS™)

SUSPENSIONS

Front Suspension	Arched double A-arm / 11 in. (27.9 cm) travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	Arched TTA with external sway bar / 11 in. (27.9 cm) travel
Rear Shocks	Twin tube gas charged shocks

TIRES / WHEELS

Front Tires / Rear Tires	Maxxis Coronado† 27 x 9 / 11 x 14 in. (68.6 x 22.9 / 27.9 x 35.6 cm)
Wheels	14 in. (35.6 cm) cast-aluminum

BRAKES

Front	Dual 220 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm disc brakes with hydraulic single-piston calipers

HIGHLIGHTS

- Dynamic Power Steering (DPS)
- Anti-Lock Braking System (ABS)
- 14 in. (35.6 cm) cast-aluminum wheels
- 27 in. (68.6 cm) Maxxis Coronado† tires
- 4,500-lb (2,041 kg) winch
- Heater-ready

DIMENSIONS / CAPACITIES

Cage	Profiled cage. ROPS approved
Estimated Dry Weight *	1,594 lb (723 kg)
L x W x H	125.7 x 64 x 80 in. (319.4 x 162.5 x 203.2 cm)
Wheelbase	83 in. (211.5 cm)
Ground Clearance	13 in. (33 cm)
Cargo Box Dimensions	38 x 54.5 x 12 in. (96.5 x 138.4 x 30.5 cm)
Cargo Box Capacity	1,000 lb (454 kg)
Power tilt bed	N/A
Tailgate Load Capacity	250 lb (113.4 kg)
Storage Capacity	Total: 6.5 gal (24.5 L)
Towing Capacity	2,500 lb (1136 kg)
Payload Capacity	1,500 lb (680 kg)
Fuel Capacity	10.6 gal (40 L)
Person Capacity	3

FEATURES

Gauge	7.6 in. (19.3 cm) wide digital display with keypad
Battery	12-V (30 amp/h)
Magneto	650-W
Instrumentation	DC outlet (10-A)
Lighting	Front lighting output 140 W LED tail lights with halo glow effect
Winch	4,500-lb (2,041 kg) winch with roller fairlead
Seat	VERSA-PRO bench seat with passenger seats flipping up, underside hooks, reinforced seat skin
Steering Wheel	Adjustable tilt steering
Protection	Integrated front steel bumper HMWPE full skid plate Front fender extension
Hitch Type	2-in hitch receiver with rear hitch, tow ball and trailer connexion
T-Cat Features	Horn, flashers and position lamps, side mirrors, license plate support, hook on front metal bumper

WARRANTY

Factory warranty	2-year BRP limited warranty
------------------	-----------------------------

BRP -Lynx-Ski Doo / T.C. Kamu Temsilcisi



arem
savunma lojistik

Web Adres
E-Posta

Telefon

: www.aremlojistik.com
: emrearslan@aremlojistik.com
: info@aremlojistik.com
: +90 212 602 AREM



MY23 TRAXTER XU HD10 T



Timeless Black

MOTOR

Tip	61 kW (82 hp) / 69 lb-ft, Rotax® 976 cc, V-twin, sıvı soğutmalı
Yakıt Dağıtım Sistemi	Elektronik Yakıt Enjeksiyonlu (EFI) Akıllı Gaz Kontrolü (iTC™)
Aktarma	PRO-TORQ CVT Hızlı Tepki Sistemi (QRS), yüksek hava akışlı havalandırma ve Elektronik Tahrik Kayışı Korumalı Ekstra L / H / N / R / P ile Şanzıman
Sürüş Tren	Seçilebilir Çim Modu / 2WD / 4WD, ABS sistemli Açık ön diferansiyel
Sürüş Asistanı	Elektronik Yokuş İnş Kontrolü ECO™ / ECO™ Kapalı / Çalışma modları Fren tutma mekanizması
Hidrolik Direksiyon	Dinamik Servo Direksiyon (DPS™)

SÜSPANSİYONLAR

Ön Süspansiyon	Kemerli çift A-kol / 11 inç (27,9 cm) hareket
Ön Şoklar	İkiz tüp gaz şarjlı şoklar
Arka Süspansiyon	Harici sallanma çubuğu / 11 inç (27,9 cm) hareket ile kemerli TTA
Arka Şoklar	İkiz tüp gaz şarjlı şoklar

LASTİKLER / TEKERLEKLER

Ön Lastikler / Arka Lastikler	Maxxis Coronado† 27 x 9 / 11 x 14 in. (68.6 x 22.9 / 27.9 x 35.6 cm)
Tekerlekler	14 in. (35.6 cm) cast-aluminum

FRENLER

Ön	Hidrolik çift pistonlu kaliperli çift 220 mm disk frenler
Arka	Hidrolik tek pistonlu kaliperli çift 220 mm disk frenler

ÖNE ÇIKAN ÖZELLİKLER

- Dinamik Servo Direksiyon (DPS)
- Kilitlemeyi Önleyici Fren Sistemi (ABS)
- 14 inç (35,6 cm) dökme alüminyum jantlar
- 27 inç (68,6 cm) Maxxis Coronado† lastikler
- 4.500 lb (2.041 kg) vinç
- Isıtıcıya hazır

BOYUTLAR / KAPASİTELER

Kafes	Profilli kafes, ROPS onaylı
Tahmini Kuru Ağırlık	1,594 lb (723 kg)
L x W x H	125.7 x 64 x 80 in. (319.4 x 162.5 x 203.2 cm)
Dingil Açıklığı	83 in. (211.5 cm)
Yerden Yükseklik	13 in. (33 cm)
Kargo Kutusu Boyutları	38 x 54.5 x 12 in. (96.5 x 138.4 x 30.5 cm)
Kargo Kutusu Kapasitesi	1,000 lb (454 kg)
Güç Eğimli Yatak	N/A
Bagaj Kapağı Yük Kapasitesi	250 lb (113.4 kg)
Depolama Kapasitesi	Total: 6.5 gal (24.5 L)
Çekme Kapasitesi	2,500 lb (1136 kg)
Yük Kapasitesi	1,500 lb (680 kg)
Yakıt Kapasitesi	10.6 gal (40 L)
Kişi Kapasitesi	3

ÖZELLİKLERİ

Ölçü	7,6 inç (19,3 cm) genişliğinde tuş takımlı dijital ekrand
Akü	12-V (30 amp/h)
Şarj Dinamosu	650-W
Enstrümantasyon	DC çıkışlı (10-A)
Aydınlatma	Ön aydınlatma çıkışı 140 W Halo parlama etkili LED arka lambalar
Vinç	4.500 lb (2.041 kg) makaralı vinç
Seat	Yukarı çevrilmiş yolcu koltukları, alt kancalar, güçlendirilmiş koltuk kaplaması ile VERSA-PRO koltuk sırası
Direksiyon	Ayarlanabilir eğimli direksiyon
Koruma	Entegre ön çelik tampon HMWPE tam koruma plakası Ön çamurluk uzantısı
Bağlantı Tipi	Arka asku, çeki topuzu ve römork bağlantısına sahip 2 inç asku alıcısı
T-Cat Özellikleri	Korna, flaşörler ve pozisyon lambaları, yan aynalar, plaka desteği, ön metal tamponda kanca

GARANTİ

2- Yıl

BRP -Lynx-Ski Doo / T.C. Kamu Temsilcisi



arem
savunma lojistik

Web Adres
E-Posta

Telefon

: www.aremlojistik.com
: emrearslan@aremlojistik.com
: info@aremlojistik.com
: +90 212 602 AREM



MY24 TRAXTER MAX XU HD10 T ABS



Stone Gray

ENGINE

Type	61 kW (82 hp) / 69 lb-ft, Rotax® 976 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PRO-TORQ CVT Transmission with Quick Response System (QRS), high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P
Drive Train	Selectable Turf Mode / 2WD / 4WD with Open front differential with ABS system
Driving Assistance	Electronic Hill Descent Control ECO™ / ECO™ Off / Work modes Brake holding mechanism
Power Steering	Dynamic Power Steering (DPS™)
Speed Category	More than 60 km/h

SUSPENSIONS

Front Suspension	Arched double A-arm / 11 in. (27.9 cm) travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	Arched TTA with external sway bar / 11 in. (27.9 cm) travel
Rear Shocks	Twin tube gas charged shocks

TIRES / WHEELS

Front Tires / Rear Tires	Maxxis Coronado† 27 x 9 / 11 x 14 in. (68.6 x 22.9 / 27.9 x 35.6 cm)
Wheels	14 in. (35.6 cm) cast-aluminum

BRAKES

Front	Dual 220 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm disc brakes with hydraulic twin-piston calipers

HIGHLIGHTS

- Dynamic Power Steering (DPS)
- Anti-Lock Braking System (ABS)
- 14 in. (35.6 cm) cast-aluminum wheels
- 27 in. (68.6 cm) Maxxis Coronado† tires
- 4,500-lb (2,041 kg) winch
- RF Digitally Encoded Security System (D.E.S.S.™)
- Heater-ready

DIMENSIONS / CAPACITIES

Cage	Profiled cage. ROPS approved
Estimated Dry Weight *	1,862 lb (845 kg)
L x W x H	153.4 x 64 x 77.5 in. (389.6 x 162.5 x 196.9 cm)
Wheelbase	115.5 in. (294 cm)
Ground Clearance	12.5 in. (31.8 cm)
Cargo Box Dimensions	38 x 54.5 x 12 in. (96.5 x 138.4 x 30.5 cm)
Cargo Box Capacity	1,000 lb (454 kg)
Power tilt bed	N/A
Tailgate Load Capacity	250 lb (113.4 kg)
Storage Capacity	Total: 11.1 gal (42.1 L)
Towing Capacity	2,500 lb (1136 kg)
Payload Capacity	1,750 lb (793,8 kg)
Fuel Capacity	10.6 gal (40 L)
Person Capacity	6

FEATURES

Gauge	7.6 in. (19.3 cm) wide digital display with keypad
Battery	12-V (30 amp/h)
Magneto	650-W
Instrumentation	DC outlet (10-A)
Lighting	Front lighting output 140 W LED tail lights with halo glow effect
Winch	4,500-lb (2,041 kg) winch with roller fairlead
Seat	VERSA-PRO bench seat with passenger seats flipping up, underside hooks, reinforced seat skin
Steering Wheel	Adjustable tilt steering
Protection	Integrated front steel bumper HMWPE full skid plate Front fender extension
Anti-Theft System	RF Digitally Encoded Security System
Hitch Type	2-in hitch receiver with rear hitch, tow ball and trailer connexion
T-Cat Features	Horn, flashers and position lamps, side mirrors, license plate support, hook on front metal bumper

WARRANTY

Factory warranty	2-year BRP limited warranty
------------------	-----------------------------



REQUEST A QUOTE



©2024 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of BRP or its affiliates. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrives GmbH. ‡All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all SSV drivers take a training course. For safety and training information, see your dealer. SSVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. SSVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any SSV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.

MY24 TRAXTER MAX XU HD10 T ABS



Stone Gray

MOTOR

Tip	61 kW (82 hp) / 69 lb-ft, Rotax® 976 cc, V-twin, sıvı soğutmalı
Yakıt Dağıtım Sistemi	Elektronik Yakıtlı Akıllı Gaz Kelebeği Kontrolü (ITC™) Enjeksiyon (EFI)
Aktarma	Hızlı Tepsisi Sistemi PRO-TORQ CVT Şanzıman (QRS), Yüksek hava akışı havalandırması ve Elektronik Tahrik Kayışı Extra L / H / N / R / P
Güç Aktarımı	ABS Sistemli, Açık ön diferansiyelli, Seçilebilir Çim Modu / 2WD / 4WD
Sürüş Asistanı	ECO™ / ECO™ Kapalı / Çalışma Modları Fren tutam mekanizması
Hidrolik Direksiyon	Dinamik Servo Direksiyon (DPS™)
Hız Kategorisi	60 km/h saatten fazla T1B

SÜSPANSİYONLAR

Ön Süspansiyon	Kemerli Çift A Kolu 11 inç. (27,9 cm) hareket mesafesi
Ön Şoklar	İkiz tüplü şarjlı şoklar
Arka Süspansiyon	Harici sallanma şubüğüne sahip Kemerli TTA / 11 inç. (27,9 cm) hareket mesafesi
Arka Şoklar	Çift tüplü gaz şarjlı şoklar

LASTİKLER / TEKERLEKLER

Ön Lastikler / Arka Lastikler	Maxxis Coronado® 27 x 9 / 11 x 14 in. (68,6 x 22,9 / 27,9 x 35,6 cm)
Tekerlekler	14 inç. (35,6 cm) dökme alüminyum

FRENLER

Ön	Hidrolik çift pistonlu kaliberlere sahip çift 220 mm disk frenler
Arka	Hidrolik çift pistonlu kaliberlere sahip çift 220 mm disk frenler

ÖNE ÇIKAN ÖZELLİKLER

- Dinamik Servo Direksiyon (DPS)
- Kilitlenmeyi Önleyici Fren Sistemi (ABS)
- 14 inç (35,6 cm) dökme alüminyum tekerlekler
- 27 inç (68,6 cm) Maxxis Coronado® lastikler
- 4,500-lb (2,041 kg) vinç
- RF Dijital Kodlu Güvenlik Sistemi (D.E.S.S.™)
- İsticuya hazır

BOYUTLAR / KAPASİTELER

Kafes	Profilli kafes ROPS onaylı
Tahmini Kuru Ağırlık *	1.862 lb (845 kg)
Ux G x Y	153.4 x 64 x 77.5 in. (389.6 x 162.5 x 196.9 cm)
Dingil Açıklığı	115.5 in. (294 cm)
Yerden Yükseklik	12.5 in. (31.8 cm)
Kargo Kutusu Boyutları	38 x 54.5 x 12 in. (96.5 x 138.4 x 30.5 cm)
Kargo Kutusu Kapasitesi	1,000 lb (454 kg)
Güç Eğimli Yatak	N/A
Bagaj Kapağı Yük Kapasitesi	250 lb (113.4 kg)
Depolama Kapasitesi	Total: 11.1 gal (42.1 L)
Çekme Kapasitesi	2,500 lb (1136 kg)
Yük Kapasitesi	1,750 lb (793,8 kg)
Yakıt Kapasitesi	10,6 gal (40 L)
Kişi Kapasitesi	6

ÖZELLİKLER

Ölçü	7.6 in. (19.3 cm) genişliğinde tuş takımlı dijital ekran
Akü	12-V (30 amp/h)
Şarj Dinamosu	650-W
Enstrümantasyon	DC çıkışı (10-A)
Aydınlatma	Ön aydınlatma çıkışı 140 W Halo parlama efektli LED arka lambalar
Vinç	Makaralı 4,500-lb (2,041 kg) vinç
Koltuk	Yukarıya doğru kaldırılabilen yolcu koltukları, alt tarafta kancaları ve güçlendirilmiş koltuk kaplaması olan VERSA-PRO koltuk sırası
Direksiyon	Ayarlanabilir eğimli direksiyon
Koruma	Entegre ön çelik tampon HMWPE tam koruma plakası Ön çamurluk uzatması
Hırsızlık Önleme Sistemi	RF Dijital Kodlu Güvenlik Sistemi
Bağlantı Tipi	Arka askı, çeki topuzu ve römork bağlantısına sahip 2 inç askı alıcısı
T-Cat Özellikleri	Korna flaşörler ve pozisyon lambaları, yan aynalar, plaka desteği, ön metal tamponda kanca

GARANTİ

2-Yıl

can-am

BRP -Lynx-Ski Doo / T.C. Kamu Temsilcisi



arem
savunma lojistik

Web Adres
E-Posta

Telefon

: www.aremlojistik.com
: emrearslan@aremlojistik.com
: info@aremlojistik.com
: +90 212 602 AREM

