



2025

COMMANDER RE



On & Off Trail
+ Mountain / Deep Snow
+ Utility
+ Family Fun



ROTAX® ENGINE

900 ACE Turbo R

Engine details	Liquid-cooled, four-stroke D.O.H.C., turbocharged
Cylinders	3
Displacement	899.0 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7900 RPM
Carburation	EFI
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	42 liters

COLOUR

Clazier Cyan / Black

DIMENSIONS

Vehicle overall length*	3240 mm
Vehicle overall width	1200 mm
Vehicle overall height	1250 mm
Ski stance	996 mm
Track nominal width	500 mm
Track nominal length	3923 mm
Track profile height	44 mm PowderMax / 38 mm Ice Cobra Silent (spring only)

POWERTRAIN

Gearbox	2F/N/R with push-button reverse
Drive clutch type	pDrive
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, aluminium master cylinder

SUSPENSION

Front suspension	LFS+ with curved lower A-Arms
Front shock	KYB PRO 36 EA-3 R Kashima
Rear suspension	EasyRide+ with adjustment
Center shock	KYB 46 Plus Kashima
Rear shock	KYB PRO 46 EA-3 R Kashima

DRY WEIGHT

Dry weight	295 kg
------------	--------

FEATURES

Frame	Radien-X	Heated grips	Standard
Skis	Blade DS+	Gauge	7.2" wide digital display / 7.8" panorama display (spring only)
Seating	Modular, 1-up heated	Windshield	Low
Handlebar	U-type steel with hooks, low grab handle	Hitch	Standard
Riser block height	145 mm	Visor Plug front / rear	Front
Starter	Electric	USB power outlet	Front
Reverse	Electromechanical	Air radiator with fan	Yes
Heated throttle lever	Standard	LinQ attachment	Multi-LinQ plate

* Vehicle overall length without snowflap.





2025

COMMANDER



On & Off Trail

+ Utility

+ Mountain / Deep Snow

+ Family Fun



ROTAX® ENGINE

600R E-TEC

900 ACE

900 ACE Turbo

Engine details

Liquid-cooled,
two-stroke, 3-D
R.A.V.E.™

Liquid-cooled,
four-stroke
D.O.H.C.

Liquid-cooled,
four-stroke
D.O.H.C., turbo-
charged

Cylinders

2

3

Displacement

599.4 cc

899.0 cc

Bore

72.3 mm

74 mm

Stroke

73 mm

69.7 mm

Maximum engine speed

8100 RPM

7250 RPM

7750 RPM

Carburation

Electronic
Direct Injection

EFI

Recommended fuel type

Unleaded

Unleaded

Minimum octane

95

95

Fuel tank

42 liters

Oil tank capacity (2-stroke)

3.4 liters

POWERTRAIN

Gearbox

2F/N/R with push-button reverse

Drive clutch type

pDrive with
clickers

pDrive with
slider shoes

pDrive

Driven clutch type

QRS

Brake system

Hydraulic brake with braided steel brake line,
aluminium master cylinder

COLOUR

Scandie Blue / Black

DIMENSIONS

Vehicle overall length*

3240 mm

Vehicle overall width

1200 mm

Vehicle overall height

1500 mm

Ski stance

996 mm

Track nominal width

500 mm

Track nominal length

3923 mm

Track profile height

44 mm PowderMax

DRY WEIGHT

Dry weight

265 kg (600R E-TEC)
277 kg (900 ACE)
289 kg (900 ACE Turbo)

SUSPENSION

Front suspension

LFS+
with curved lower
A-Arms

Front shock

KYB 36

Rear suspension

Articulated EasyRide+
with adjustment

Center shock

KYB 36

Rear shock

KYB 36

FEATURES

Frame

Radien-X

Skis

Blade DS+

Seating

Modular, 1-up

Handlebar

U-type steel with hooks, low grab
handle

Riser block height

145 mm

Starter

Electric and manual (E-TEC)
Electric (ACE)

Reverse

RER (E-TEC)
Electromechanical (ACE)

Heated throttle lever

Standard

Heated grips

Standard

Gauge

4.5" digital display

Windshield

Extra high with side deflectors

Hitch

Standard

Visor Plug front / rear

Front

USB power outlet

Front

Air radiator with fan

Yes

LinQ attachment

Multi-LinQ plate

* Vehicle overall length without snowflap.

©2024 Bombardier Recreational Products Inc., (BRP). All rights reserved. ™, ® and the BRP logo are trademarks of BRP or its affiliates.

†All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation.

A BRP BRAND



COMMANDER LIMITED



ROTAX® ENGINE

900 ACE

900 ACE Turbo

COLOUR

Noble Bronze / Black

Engine details

Liquid-cooled, four-stroke D.O.H.C.

Liquid-cooled, four-stroke D.O.H.C., turbocharged

Cylinders

3

Displacement

899.0 cc

Bore

74 mm

Stroke

69.7 mm

Maximum engine speed

7250 RPM

7750 RPM

Carburation

EFI

Recommended fuel type

Unleaded

Minimum octane

95

Fuel tank

42 liters

DIMENSIONS

Vehicle overall length*

3240 mm

Vehicle overall width

1200 mm
1280 mm (w. 2up seat)

Vehicle overall height

1500 mm

Ski stance

996 mm
1097 mm (w. 2up seat)

Track nominal width

500 mm

Track nominal length

3923 mm

Track profile height

44 mm PowderMax /
38 mm Ice Cobra Silent
(spring only)

POWERTRAIN

Gearbox

2F/N/R with push-button reverse

Drive clutch type

pDrive with slider shoes

pDrive

Driven clutch type

QRS

Brake system

Hydraulic brake with braided steel brake line,
aluminium master cylinder

SUSPENSION

Front suspension

LFS+ with curved lower
A-Arms (1-up)
LFS+ (2-up)

Front shock

KYB 36 Plus (1-up)
KYB 36 Plus R (2-up)

Rear suspension

Articulated EasyRide+
with adjustment

Center shock

KYB 46 Plus Kashima

Rear shock

KYB 46 Plus Kashima

DRY WEIGHT

Dry weight

287 kg (1 up)
298 kg (2 up)

298 kg (1 up)
309 kg (2 up)

FEATURES

Frame

Radien-X

Skis

Blade DS+

Seating

Modular, 1-up or 2-up
heated

Handlebar

U-type steel with hooks,
low grab handle

Riser block height

145 mm

Starter

Electric

Reverse

Electromechanical

Heated throttle lever

Standard

Heated grips

Standard

Gauge

7.2" wide digital display

Windshield

Extra high with side deflectors

Hitch

Standard

Visor Plug front / rear

Front and rear (2-up)

USB power outlet

Front

Air radiator with fan

Yes

LinQ attachment

Multi-LinQ plate

* Vehicle overall length without snowflap.

