

# 49 RANGER



Mountain / Deep Snow  
+ On & Off Trail  
+ Utility



## ROTAX® ENGINE

### 600 ACE

### 600 EFI

#### Engine details

Liquid-cooled, four-stroke D.O.H.C.

Liquid-cooled, two-stroke

#### Cylinders

2

#### Displacement

600 cc

599.4 cc

#### Bore

74 mm

72.3 mm

#### Stroke

69.7 mm

73 mm

#### Maximum engine speed

7250 RPM

7500 RPM

#### Carburation

EFI

#### Recommended fuel type

Unleaded

#### Minimum octane

95

#### Fuel tank

37 liters

## COLOUR

Viper Red / Black

## DIMENSIONS

Vehicle overall length\* 3330 mm (ACE)  
3270 mm (EFI)

Vehicle overall width 1200 mm

Vehicle overall height 1340 mm

Ski stance 996 mm

Track nominal width 406 mm

Track nominal length 3923 mm

Track profile height 38 mm DSG

## POWERTRAIN

#### Drive clutch type

eDrive II

pDrive

#### Driven clutch type

QRS

#### Brake system

Hydraulic brake with braided steel brake line, aluminium master cylinder

## SUSPENSION

Front suspension LFS+

Front shock KYB 36

Rear suspension PPS<sup>2</sup>-DS+

Center shock KYB 36

Rear shock KYB 36

## DRY WEIGHT

#### Dry weight

238 kg

229 kg

## FEATURES

Frame Radien (EFI)  
Radian-X (ACE)

Skis Blade DS+

Seating Sport, 1-up

Handlebar U-type steel with hooks

Riser block height 145 mm

Starter Electric and manual (EFI)  
Electric (ACE)

Reverse RER (EFI)  
Mechanical (ACE)

Heated throttle lever Standard

Heated grips Standard

Gauge 4.5" digital display

Windshield Medium with side deflectors

Visor Plug front / rear Front

USB power outlet Yes, in front compartment

Air radiator with fan Yes

LinQ attachment Multi-LinQ plate

\* Vehicle overall length without snowflap.



2025

# 49 RANGER PRO



Mountain / Deep Snow  
+ Steep and deep  
+ On & Off Trail  
+ Utility



Orange/Full Moon  
Silver/Black

ROTAX® ENGINE	600R E-TEC	850 E-TEC
Engine details	Liquid-cooled, two-stroke, 3-D R.A.V.E.™	
Cylinders	2	
Displacement	599.4 cc	849 cc
Bore	72.3 mm	82 mm
Stroke	73 mm	80.4 mm
Maximum engine speed	8100 RPM	7900 RPM
Carburation	Electronic Direct Injection	Electronic Direct Injection with additional booster injectors
Recommended fuel type	Unleaded	
Minimum octane	95	
Fuel tank	37 liters	
Oil tank capacity (2-stroke)	3.4 liters	

POWERTRAIN	
Drive clutch type	pDrive with clickers
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, aluminium master cylinder

DRY WEIGHT		
Dry weight	240 kg	249 kg

FEATURES			
Frame	Radien <sup>2</sup>	Heated grips	Standard
Skis	Blade DS+	Gauge	7.2" wide digital display
Seating	Sport, 1-up heated	Windshield	Medium with side deflectors
Handlebar	U-type steel with hooks, low grab handle	Hitch	Standard
Riser block height	145 mm	Visor Plug front / rear	Front
Starter	Electric and manual	USB power outlet	Yes, in front compartment
Reverse	RER	Air radiator with fan	Yes
Heated throttle lever	Standard	LinQ attachment	Multi-LinQ plate

\* Vehicle overall length without snowflap.

