

ROTAX® ENGINE	900 ACE
Engine details	Liquid-cooled, four-stroke D.O.H.C.
Cylinders	3
Displacement	899.0 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7250 RPM
Carburation	EFI
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	42 liters

COLOUR	White/Orange/Black	
DIMENSIONS		
Vehicle overall length*	3240 mm	
Vehicle overall width	1280 mm	
Vehicle overall height	1470 mm	
Ski stance	1080 mm	
Track nominal width	500 mm	
Track nominal length	3923 mm	
Track profile height	38 mm Ice Cobra silent (studded)	

2F/N/R with push-button reverse
pDrive with slider shoes
QRS
Hydraulic brake with braided steel brake line, aluminium master cylinder

LFS
KYB 36
Articulated EasyRide+ with adjustment & extension lock
KYB 36
KYB 36

DRY WEIGHT

Dry weight 291 kg

FEATURES

Blade DS+	
Modular, 1-up heated	
U-type steel with hooks, low grab handle	
145 mm	
Electric	
Electromechanical	

Heated throttle lever	Standard	
Heated grips	Standard	
Gauge	7.2" wide digital display	
Windshield	Extra high with side deflectors	
Hitch	Standard	
Visor Plug front / rear	Front and rear	
USB power outlet	Yes, in front compartment	
Air radiator with fan	Yes	



 $^{^{}st}$ Vehicle overall length without snowflap.



ROTAX® ENGINE	600 ACE	600 EFI
Engine details	Liquid-cooled, four- stroke D.O.H.C.	Liquid-cooled, two-stroke
Cylinders	2	2
Displacement	600 cc	599.4 cc
Bore	74 mm	72.3 mm
Stroke	69.7 mm 73 mm	
Maximum engine speed	7250 RPM 7500 RPM	
Carburation	EFI	
Recommended fuel type	Unleaded	
Minimum octane	95	
Fuel tank	42 liters	
Oil tank capacity (2-stroke)	3.4 liters	

COLOUR	Viper Red / Black
DIMENSIONS	
Vehicle overall length*	3240 mm
Vehicle overall width	1200 mm
Vehicle overall height	1500 mm
Ski stance	996 mm
Track nominal width	500 mm
Track nominal length	3923 mm
Track profile height	38 mm

POWERTRAIN

Drive clutch type	eDrive II	pDrive
Driven clutch type	QRS	
Brake system	Hydraulic brake with braided steel brake line, aluminium master cylinder	

SUSPENSION

Front suspension	LFS+	
Front shock	KYB 36	
Rear suspension	EasyRide+	
Center shock	KYB 36	
Rear shock	KYB 36	

DRY WEIGHT

|--|

FEATURES

Frame	Radien-X	
Skis	Blade DS+	
Seating	Modular, 1-up	
Handlebar	U-type steel with hooks	
Riser block height	145 mm	
Starter	Electric and manual (EFI) Electric (ACE)	
Reverse	RER (EFI) Electromechanical (ACE)	

Heated throttle lever	Standard
Heated grips	Standard
Gauge	4.5" digital display
Windshield	Extra high with side deflectors
Visor Plug front / rear	Front
USB power outlet	Yes, in front compartment
Air radiator with fan	Yes
LinQ attachment	Multi-LinQ plate



^{*} Vehicle overall length without snowflap.



ROTAX® ENGINE 600 ACE Engine details Liquid-cooled, four-stroke D.O.H.C. Cylinders 600 cc Displacement Bore 74 mm Stroke 69.7 mm Maximum engine speed 7250 RPM Carburation Recommended fuel type Unleaded Minimum octane 95 Fuel tank 42 liters

	Orange/
COLOUR	Full Moon Silver/Black

DIMENSIONS	
Vehicle overall length*	3240 mm
Vehicle overall width	1200 mm
Vehicle overall height	1500 mm
Ski stance	996 mm
Track nominal width	500 mm
Track nominal length	3923 mm
Track profile height	44 mm

POWERTRAIN

Gearbox	2F/N/R with push-button reverse
Drive clutch type	eDrive II
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, aluminium master cylinder

SUSPENSION

Front suspension	LFS+ with curved lower A-Arms
Front shock	KYB 36
Rear suspension	Articulated EasyRide+ with adjustment
Center shock	KYB 36
Rear shock	KYB 36

DRY WEIGHT

Dry weight 263 kg

FEATURES

Frame	Radien-X
Skis	Blade DS+
Seating	Modular, 1-up heated
Handlebar	U-type steel with hooks, low grab handle
Riser block height	145 mm
Starter	Electric
Reverse	Electromechanical

Heated throttle lever	Standard
Heated grips	Standard
Gauge	7.2" wide digital display
Windshield	Extra high with side deflectors
Hitch	Standard
Visor Plug front / rear	Front
USB power outlet	Yes, in front compartment
Air radiator with fan	Yes
LinQ attachment	Multi-LinQ plate



^{*} Vehicle overall length without snowflap.