



2025



ROTAX® ENGINE	850 E-TEC Turbo R
Engine details	Liquid-cooled, two-stroke, turbocharged, water injection system, 3-D R.A.V.E.™
Cylinders	2
Displacement	849 cc
Bore	82 mm
Stroke	80.4 mm
Maximum engine speed	7900 RPM
Carburation	Electronic Direct Injection with additional booster injectors
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	37 liters
Oil tank capacity (2-stroke)	3.4 liters

Race Orange / Black
3040 mm
1270 mm
1140 mm
1097 mm
381 mm
3487 mm
38 mm Ice Ripper XT studded

**SUSPENSION** 

# **POWERTRAIN**

Drive clutch type	pDrive with clickers
Driven clutch type	QRS
Brake system	RS brake with 4 piston caliber, adjustable brake lever, aluminium master cylinder

Front suspension	LFS+
Front shock	KYB PRO 46 HLCR Kashima
Rear suspension	PPS <sup>3</sup>
Center shock	KYB PRO 46 HLCR Kashima
Rear shock	KYB PRO 46 HLCR Kashima

### **DRY WEIGHT**

241 kg **Dry weight** 

#### **FEATURES**

Frame	Radien²
Skis	Blade XC+
Seating	Sport, 1-up
Handlebar	U-type aluminium with hooks
Riser block height	90 mm
Starter	Manual with SHOT
Reverse	RER

Heated throttle lever	Standard	
Heated grips	Standard	
Gauge	10.25" Touchscreen Display	
Windshield	Low	
USB power outlet	Yes, in front compartment	
LinQ attachment	2 pairs	



<sup>\*</sup> Vehicle overall length without snowflap.







2025

600R E-TEC	850 E-TEC
Liquid-cooled, two-	stroke, 3-D R.A.V.E.™
	2
599.4 cc	849 cc
72.3 mm	82 mm
73 mm	80.4 mm
8100 RPM	7900 RPM
Electronic Direct Injection	Electronic Direct Injection with additional booster injectors
Unle	eaded
95	
37 liters	
3.4 liters	
	Liquid-cooled, two- 599.4 cc 72.3 mm 73 mm 8100 RPM  Electronic Direct Injection  Unle

COLOUR	Viper Red/Black
DIMENSIONS	
Vehicle overall length*	3040 mm
Vehicle overall width	1270 mm
Vehicle overall height	1140 mm
Ski stance	1097 mm
Track nominal width	381 mm
Track nominal length	3487 mm
Track profile height	41 mm Cobra 38 mm Ice Ripper XT studded (spring only)

## **POWERTRAIN**

Drive clutch type	pDrive with clickers
Driven clutch type	QRS
Brake system	RS brake with 4 piston caliber, adjustable brake lever, aluminium master cylinder
DRY WEIGHT	

220 kg

Front suspension	LFS+
Front shock	KYB PRO 46 HLCR Kashima
Rear suspension	PPS <sup>3</sup>
Center shock	KYB PRO 46 HLCR Kashima

KYB PRO 46 HLCR

Kashima

#### **FEATURES**

**Dry weight** 

Frame	Radien²
Skis	Blade XC+
Seating	Sport, 1-up
Handlebar	U-type aluminium with hooks
Riser block height	90 mm
Starter	Manual Electric (spring only)
Reverse	RER

Standard
7.2" wide digital display / 10.25" Touchscreen Display (spring only)
Low
Yes, in front compartment
2 pairs

**SUSPENSION** 

**Rear shock** 

231 kg



<sup>\*</sup> Vehicle overall length without snowflap.



ROTAX® ENGINE	600R E-TEC
Engine details	Liquid-cooled, two-stroke, 3-D R.A.V.E.™
Cylinders	2
Displacement	599.4 cc
Bore	72.3 mm
Stroke	73 mm
Maximum engine speed	8100 RPM
Carburation	Electronic Direct Injection
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	37 liters
Oil tank capacity (2-stroke)	3.4 liters

COLOUR	Viper Red/Black
DIMENSIONS	
Vehicle overall length*	2920 mm
Vehicle overall width	1270 mm
Vehicle overall height	1140 mm
Ski stance	1097 mm
Track nominal width	381 mm
Track nominal length	3269 mm
Track profile height	41 mm Cobra

#### **POWERTRAIN**

Drive clutch type	pDrive with clickers
Driven clutch type	QRS
Brake system	RS brake with 4 piston caliber, adjustable brake lever, aluminium master cylinder

# DRY WEIGHT Dry weight 219 kg

#### **SUSPENSION**

Front suspension	LFS+
Front shock	KYB PRO 46 HLCR Kashima
Rear suspension	PPS <sup>3</sup>
Center shock	KYB PRO 46 HLCR Kashima
Rear shock	KYB PRO 46 HLCR Kashima

#### **FEATURES**

Frame	Radien²
Skis	Blade XC+
Seating	Sport, 1-up
Handlebar	U-type aluminium with hooks
Riser block height	90 mm
Starter	Manual
Reverse	RER

Heated throttle lever	Standard
Heated grips	Standard
Gauge	7.2" wide digital display
Windshield	Low
USB power outlet	Yes, in front compartment
LinQ attachment	1 pair
LinQ attachment	1 pair



<sup>\*</sup> Vehicle overall length without snowflap.