



2025

# SHREDDER DS



Steep and deep  
+ Mountain / Deep Snow



Hot Chili Metallic / Black  
Black (spring only on  
Turbo models)



## ROTAX® ENGINE

### 850 E-TEC

### 850 E-TEC Turbo R

## COLOUR

### Engine details

Liquid-cooled, two-  
stroke, 3-D R.A.V.E.™

Liquid-cooled,  
two-stroke,  
turbocharged,  
3-D R.A.V.E.™

## DIMENSIONS

### Cylinders

2

### Displacement

849 cc

### Bore

82 mm

### Stroke

80.4 mm

### Maximum engine speed

7900 RPM

### Carburation

Electronic Direct Injection with  
additional booster injectors

### Recommended fuel type

Unleaded

### Minimum octane

95

### Fuel tank

37 liters

### Oil tank capacity (2-stroke)

3.4 liters

### Vehicle overall length\*

3190 mm (3900)  
3335 mm (4100)

### Vehicle overall width

1055 mm

### Vehicle overall height

1280 mm

### Ski stance

863 mm

### Track nominal width

381 mm

### Track nominal length

3912 mm  
4178 mm (spring only)

### Track profile height

76 mm PowderMax  
X-Light

## POWERTRAIN

### Drive clutch type

pDrive with clickers

### Driven clutch type

QRS

### Brake system

Hydraulic brake with braided steel  
brake line, adjustable brake lever,  
aluminium master cylinder

## SUSPENSION

### Front suspension

LFS

### Front shock

KYB 36 Plus Kashima

### Rear suspension

PPS²-DS+

### Center shock

KYB 36 Plus Kashima

### Rear shock

KYB 36 Plus Kashima

## DRY WEIGHT

### Dry weight

3900: 204 kg

3900: 211 kg  
4100: 216 kg

## FEATURES

### Frame

Radien²

### Skis

Blade DS+

### Seating

Mountain Light, 1-up

### Handlebar

U-type aluminium with hooks,  
low grab handle

### Riser block height

120 mm

### Starter

Manual with SHOT  
Electric (spring only on 3900)

### Reverse

RER

### Heated throttle lever

Standard

### Heated grips

Standard

### Gauge

4.5" digital display /  
10.25" Touchscreen Display  
(spring only)

### USB power outlet

Yes, in front compartment

### LinQ attachment

2 pairs

\* Vehicle overall length without snowflap.



2025

# SHREDDER



Steep and deep  
+ Mountain / Deep Snow



## ROTAX® ENGINE

### 600R E-TEC

Engine details	Liquid-cooled, two-stroke, 3-D R.A.V.E.™
Cylinders	2
Displacement	599.4 cc
Bore	72.3 mm
Stroke	73 mm
Maximum engine speed	8100 RPM
Carburation	Electronic Direct Injection
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	37 liters
Oil tank capacity (2-stroke)	3.4 liters

## COLOUR

Viper Red / Black

## DIMENSIONS

Vehicle overall length*	3060 mm (3700) 3190 mm (3900)
Vehicle overall width	1120 mm
Vehicle overall height	1280 mm
Ski stance	921 mm
Track nominal width	381 mm
Track nominal length	3705 mm 3923 mm
Track profile height	64 mm PowderMax

## POWERTRAIN

Drive clutch type	pDrive with clickers
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, aluminium master cylinder

## SUSPENSION

Front suspension	LFS
Front shock	KYB 36
Rear suspension	PPS <sup>2</sup> -DS+
Center shock	KYB 36
Rear shock	KYB 36

## DRY WEIGHT

Dry weight	3700: 194 kg 3900: 198 kg
------------	------------------------------

## FEATURES

Frame	Radien <sup>2</sup>	Reverse	RER
Skis	Blade DS+	Heated throttle lever	Standard
Seating	Mountain Light, 1-up	Heated grips	Standard
Handlebar	U-type aluminium with hooks, low grab handle	Gauge	4.5" digital display
Riser block height	120 mm	USB power outlet	Yes, in front compartment
Starter	Manual Electric (spring only)	LinQ attachment	2 pairs

\* Vehicle overall length without snowflap.



2025

# SHREDDER RE



Steep and deep  
+ Mountain / Deep Snow



Viper Red / Black  
Black (spring only on Turbo models)



## ROTAX® ENGINE

### 600R E-TEC

### 850 E-TEC

### 850 E-TEC Turbo R

#### Engine details

Liquid-cooled, two-stroke, 3-D  
R.A.V.E.™

Liquid-cooled,  
two-stroke,  
turbocharged,  
3-D R.A.V.E.™

#### Cylinders

2

#### Displacement

599.4 cc

849 cc

#### Bore

72.3 mm

82 mm

#### Stroke

73 mm

80.4 mm

#### Maximum engine speed

8100 RPM

7900 RPM

#### Carburation

Electronic  
Direct Injection

Electronic Direct Injection with  
additional booster injectors

#### Recommended fuel type

Unleaded

#### Minimum octane

95

#### Fuel tank

37 liters

#### Oil tank capacity (2-stroke)

3.4 liters

## COLOUR

## DIMENSIONS

Vehicle overall length\* 3060 mm (3700)  
3190 mm (3900)

Vehicle overall width 1120 mm

Vehicle overall height 1280 mm

Ski stance 921 mm

Track nominal width 381 mm

Track nominal length 3705 mm  
3923 mm (64mm)  
3912 mm (76mm)

Track profile height 64 mm PowderMax  
76 mm PowderMax X-Light  
(spring only 3900)

## POWERTRAIN

#### Drive clutch type

pDrive with clickers

#### Driven clutch type

QRS

#### Brake system

Hydraulic brake with braided steel brake line,  
adjustable brake lever, aluminium master cylinder

## SUSPENSION

Front suspension LFS

Front shock KYB PRO 40 EA-3 Kashima

Rear suspension PPS<sup>2</sup>-DS+

Center shock KYB 46 Plus Kashima

Rear shock KYB PRO 46 EA-3 R Kashima

## DRY WEIGHT

#### Dry weight

3700: 208 kg

3700: 215 kg  
3900: 219 kg

3700: 222 kg  
3900: 226 kg

## FEATURES

#### Frame

Radien<sup>2</sup>

#### Skis

Blade DS+

#### Seating

Mountain Light, 1-up

#### Handlebar

U-type aluminium with hooks,  
low grab handle

#### Riser block height

120 mm

#### Starter

Manual with SHOT  
Electric (spring only on 3700)

#### Reverse

RER

#### Heated throttle lever

Standard

#### Heated grips

Standard

#### Gauge

4.5" digital display /  
10.25" Touchscreen Display  
(spring only)

#### USB power outlet

Yes, in front compartment

#### LinQ attachment

2 pairs

\* Vehicle overall length without snowflap.

©2024 Bombardier Recreational Products Inc., (BRP). All rights reserved.™,\* and the BRP logo are trademarks of BRP or its affiliates.

\*All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation.

